

(19) World Intellectual Property
Organization
International Bureau




(43) International Publication Date
5 February 2004 (05.02.2004)

PCT

(10) International Publication Number
WO 2004/010823 A1

- (51) International Patent Classification⁷: **A47B 3/08** (74) Agent: **BRIDGE-BUTLER, Alan, James**; G.F. Redfern & Co., 7 Staple Inn, Holborn, London WC1V 7QF (GB).
- (21) International Application Number: **PCT/GB2003/003064** (81) Designated States (*national*): **AU, US, ZA.**
- (22) International Filing Date: **15 July 2003 (15.07.2003)** (84) Designated States (*regional*): **European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR).**
- (25) Filing Language: **English**
- (26) Publication Language: **English**
- (30) Priority Data: **0217385.4** **26 July 2002 (26.07.2002)** **GB**
- (71) Applicant (*for all designated States except US*): **GOPAK LIMITED** [GB/GB]; Range Road, Hythe, Kent CT21 6HG (GB).
- (72) Inventor; and
- (75) Inventor/Applicant (*for US only*): **LE FLEMMING SHEPHERD, Peter, Stanley** [GB/GB]; Spindrifft, Cliff Road, Hythe, Kent CT21 5XQ (GB).
- Declarations under Rule 4.17:**
- *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AU, ZA, European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR)*
- *of inventorship (Rule 4.17(iv)) for US only*
- Published:**
- *with international search report*
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: **STANCHION SUPPORT**



(57) Abstract: A sliding pivot means for a support element (9) which is used with a stanchion (2) which is hinged to the item (1) with which it is used and from which it can be unfolded, in which one end (5a) of the support element (5) is rigidly attached to the stanchion (2) and the opposite end is provided with a substantially transverse portion (7) extending therefrom, comprises a slide (9), a sleeve (10) provided with a slide pin (11) extending in substantially the same plane as the sleeve (10), and a socket (12) substantially parallel with said transverse portion (7), and in which the sleeve (10) is located on the transverse portion (7), and the pin (11) is located in the slide (9), the sleeve (10) being adapted to rotate about the transverse portion (9), and the pin (11) to rotate in the slide (9), the pin (11) moving along the slide (9) when the stanchion (2) is rotated about its hinge (4), and the socket (12) being adapted to receive the transverse portion (7) when the stanchion (2) is in a fully unfolded position.



WO 2004/010823 A1